WHAT IS CLAIMED IS:

1. An electrophotographic endless belt comprising a beltlike substrate and a meandering-preventive member attached to the inner peripheral surface of the beltlike substrate via a pressure-sensitive adhesive double-coated tape; said pressure-sensitive adhesive double-coated tape being a pressure-sensitive adhesive double-coated tape having i) a reinforcing base material and ii) pressure-sensitive adhesive layers on both sides of the reinforcing base material; wherein;

said reinforcing base material has a thickness of from 25 μm or more to 200 μm or less;

said pressure-sensitive adhesive layers on both sides each have a thickness of 200 μm or less and at least one of said pressure-sensitive adhesive layers has a thickness of from more than 100 μm to 200 μm or less; and

said meandering-preventive member has a hardness of from 15° or more to 70° or less.

2. The electrophotographic endless belt according to claim 1, wherein at least one of said pressure-sensitive adhesive layers has a thickness of from 110 μm or more to 190 μm or less.

3. The electrophotographic endless belt

according to claim 1, wherein said meandering-preventive member has a hardness of from 20° or more to 60° or less.

4. The electrophotographic endless belt according to claim 1, wherein said meandering-preventive member has a working precision of 0.2 mm or less.

5. The electrophotographic endless belt according to claim 1, which is an intermediate transfer belt.

6. A process cartridge comprising an electrophotographic endless belt and being detachably mountable to the main body of an electrophotographic apparatus;

said electrophotographic endless belt comprising a beltlike substrate and a meandering-preventive member attached to the inner peripheral surface of the beltlike substrate via a pressure-sensitive adhesive double-coated tape; said pressure-sensitive adhesive double-coated tape being a pressure-sensitive adhesive double-coated tape having i) a reinforcing base material and ii) pressure-sensitive adhesive layers on both sides of the reinforcing base material; wherein;

said reinforcing base material has a thickness of from 25 μm or more to 200 μm or less;

said pressure-sensitive adhesive layers on both sides each have a thickness of 200 μm or less and at least one of said pressure-sensitive adhesive layers has a thickness of from more than 100 μm to 200 μm or less; and

said meandering-preventive member has a hardness of from 15° or more to 70° or less.

7. The process cartridge according to claim 6, wherein said electrophotographic endless belt is an intermediate transfer belt.

8. The process cartridge according to claim 7, which further comprises an electrophotographic photosensitive member.

9. An electrophotographic apparatus comprising:

an electrophotographic photosensitive member;

a charging means for charging the electrophotographic photosensitive member electrostatically;

an exposure means for forming an electrostatic latent image on the electrophotographic photosensitive member having been charged by the charging means;

a developing means for developing the electrostatic latent image formed on the electrophotographic photosensitive member by the exposure means, to form a toner image on the electrophotographic photosensitive member;

an intermediate transfer belt which is to form a contact zone between itself and the electrophotographic photosensitive member, for secondarily transferring to a transfer material the toner image transferred after the toner image has been primarily transferred thereto from the electrophotographic photosensitive member; and

a primary transfer means for transferring the toner image primarily from the electrophotographic photosensitive member to the intermediate transfer belt at the contact zone therebetween;

said intermediate transfer belt comprising a beltlike substrate and a meandering-preventive member attached to the inner peripheral surface of the beltlike substrate via a pressure-sensitive adhesive double-coated tape; said pressure-sensitive adhesive double-coated tape being a pressure-sensitive adhesive double-coated tape having i) a reinforcing base material and ii) pressure-sensitive adhesive layers on both sides of the reinforcing base material; wherein;

said reinforcing base material has a thickness

of from 25 μm or more to 200 μm or less;

said pressure-sensitive adhesive layers on both sides each have a thickness of 200 μm or less and at least one of said pressure-sensitive adhesive layers has a thickness of from more than 100 μm to 200 μm or less; and

said meandering-preventive member has a hardness of from 15° or more to 70° or less.

10. The electrophotographic apparatus according to claim 9, which comprises a process cartridge integrally supporting at least said electrophotographic photosensitive member and said intermediate transfer belt and being detachably mountable to the main body of the electrophotographic apparatus.